



# Z300 Series



# SPECIFICATIONS

## Specifications

Model		ZG327		ZG332		ZD323		
		ZG327PA-60	ZG327RPA-60R	ZG332P-60	ZG332LP-72	ZD323-60		
<b>Engine</b>	Model	Kubota KGZ770-E2-MA1	Kubota KG770-E2-MA1	Kubota WG972-G-E3-ZG-1		Kubota D902-E3-ZD		
	Type	Gasoline, air-cooled V-Twin with heavy-duty canister air filter		Gasoline, liquid-cooled (3 cyl.)		Diesel, liquid-cooled (3 cyl.)		
	Max. horsepower (Gross)	27HP@3600 rpm		32.5HP@3600rpm		23HP@3200rpm		
	Total displacement	cu.in. (cc)	46.9 (768)		58.7 (962)		54.8 (898)	
	Starting system	Key switch					Key switch - super glow	
<b>Dimensions</b>	Overall length	in. (mm)	87.8 (2230)		91.7 (2329)	95.0 (2414)	87.4 (2220)	
	Overall width	(w/ mower)	in. (mm)	75.2 (1911)	63.1 (1604)	75.2 (1911)	87.6 (2224)	72.8 (1850)
		(w/o mower)	in. (mm)	57.5 (1460)				
	Overall height	(w/ ROPS upright)	in. (mm)	75.4 (1915)				
(w/ ROPS folded)		in. (mm)	61.2 (1555)		64.8 (1645)		61.2 (1555)	
<b>Wheel base</b>		in. (mm)	55.5 (1410)		52.5 (1333)	58.9 (1495)	55.5 (1410)	
<b>Tread</b>	Front	in. (mm)	38.4 (975)			42.1 (1070)	38.4 (975)	
	Rear	in. (mm)	45.3 (1150)					
<b>Tire size</b>	Front		15 x 6.0-6 Non-flat			15 x 6.0-6 Pneumatic		
	Rear		26 x 12.0-12					
<b>Weight (w/ mower)</b>	lbs. (kg)	1565 (710)		1651 (749)	1763 (800)	1645 (746)		
<b>Transmission system</b>	2-HST w/ Gear reduction							
<b>Speed control</b>	2-hand lever							
<b>Travel speed range</b>	Forward	mph (km/h)	0-10.6 (0-17.0)			0-9.3 (0-15.0)		
	Reverse	mph (km/h)	0-5.3 (0-8.5)			0-5.2 (0-8.3)		
<b>Brake type</b>	Wet multi disks, foot applied, released							
<b>PTO</b>	Type	Shaft drive						
	Clutch type	Hydraulic independent PTO clutch with wet multi disks						
	PTO brake	Wet single disk						
<b>Mower deck</b>	Model	RCK60P-327Z	RCK60P-331Z	RCK60P-327Z	RCK72P-332Z	RCK60P-331Z		
	Mower lift system	Hydraulic						
	Mower deck type	Pro commercial - Fabricated deck						
	Deck depth	in. (mm)	6.5 (165)	5.5 (140)	6.5 (165)			
	Belt type	Multi-Belt						
	Deck steel thickness	in. (mm)	0.17 (4.2)					
	Anti-scalp roller		Rigid	Swivel	Rigid	Swivel		
	Cutting width of mower		60 in.			72 in.	60 in.	
	Number of blades	3 blades						
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments						
	Mounting system of mower	Quick joint, parallel linkage						
	Blade tip speed (max.)		18100 FPM	17100 FPM	18100 FPM	18200 FPM	18100 FPM	
	<b>Engine stop system</b>	Key stop						
<b>Fuel tank capacity</b>	gals. (ltrs.)	12.7 (48)				12.9 (49)		
<b>Battery</b>	U1L10 (12V, RC: 22 min., CCA: 300, CA: 365)			51R (12V, RC: 70 min., CCA: 475A)				
<b>Alternator capacity</b>	13.4 Amps at 12 Volts			14 Amps at 14 Volts				
<b>Water temperature indicator</b>	-			Standard				
<b>Hour meter</b>	Standard							
<b>Fuel gauge</b>	Electric							

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.



# Z300 Series



# SPECIFICATIONS

## Specifications

Model		ZD326			
		ZD326S-60	ZD326P-60	ZD326RP-60R	
<b>Engine</b>	Model	Kubota D1005-E3-ZD-2			
	Type	Diesel, liquid-cooled (3 cyl.)			
	Max. horsepower (Gross)	26HP @ 3200rpm			
	Total displacement	cu.in. (cc)	61.1 (1001)		
	Starting system	Key switch - super glow			
<b>Dimensions</b>	Overall length	in. (mm)	87.4 (2220)		
	Overall width	(w/ mower)	in. (mm)	75.2 (1911)	
		(w/o mower)	in. (mm)	57.5 (1460)	
	Overall height	(w/ ROPS upright)	in. (mm)	75.4 (1915)	
(w/ ROPS folded)		in. (mm)	61.2 (1555)		
<b>Wheel base</b>		in. (mm)	55.5 (1410)		
<b>Tread</b>	Front	in. (mm)	38.4 (975)		
	Rear	in. (mm)	45.3 (1150)		
<b>Tire size</b>	Front		15 × 6.0-6 Pneumatic	15 × 6.0-6 Non-Flat	
	Rear		26 × 12.0-12		
<b>Weight (w/ mower)</b>	lbs. (kg)	1667 (756)	1700 (771)	1667 (756)	
<b>Transmission system</b>		2-HST w/ Gear reduction			
<b>Speed control</b>		2-hand lever			
<b>Travel speed range</b>	Forward	mph (km/h)	0-9.3 (0-15.0)	0-10.6 (0-17.0)	
	Reverse	mph (km/h)	0-5.2 (0-8.3)	0-5.3 (0-8.5)	
<b>Brake type</b>		Wet multi disks, foot applied, released			
<b>PTO</b>	Type	Shaft drive			
	Clutch type	Hydraulic independent PTO clutch with wet multi disks			
	PTO brake	Wet single disk			
<b>Mower deck</b>	Model		RCK60P-331Z	RCK60R-331Z	
	Mower lift system		Hydraulic		
	Mower deck type		Pro commercial—Fabricated deck		
	Deck depth	in. (mm)	6.5 (165)	5.5 (140)	
	Belt type		Multi-Belt		
	Deck steel thickness	in. (mm)	0.17 (4.2)		
	Anti-scalp roller		Swivel		
	Cutting width of mower		60 in.		
	Number of blades		3 blades		
	Cutting height		1 in. ~ 5 in. / 1/4 in. increments		
	Mounting system of mower		Quick joint, parallel linkage		
	Blade tip speed (max.)		18100 FPM	17100 FPM	
<b>Engine stop system</b>		Key stop			
<b>Fuel tank capacity</b>	gals. (ltrs.)	12.9 (49)			
<b>Battery</b>		51R (12V, RC: 70 min., CCA: 475A)			
<b>Alternator capacity</b>		14 Volts at 14 Amps			
<b>Water temperature indicator</b>		Standard			
<b>Hour meter</b>		Standard			
<b>Fuel gauge</b>		Electric			

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.



# Z300 Series



# SPECIFICATIONS

## Specifications

Model		ZD331				
		ZD331P-60	ZD331LP-72	ZD331RP-60R		
<b>Engine</b>	Model	Kubota D1305-E3-ZD				
	Type	Diesel, liquid-cooled (3 cyl.)				
	Max. horsepower (Gross)	31HP @ 3000rpm				
	Total displacement	cu.in. (cc)	77.0 (1261)			
	Starting system	Key switch - super glow				
<b>Dimensions</b>	Overall length	in. (mm)	87.4 (2220)	91.9 (2335)	87.4 (2220)	
	Overall width	(w/ mower)	in. (mm)	75.2 (1911)	87.6 (2224)	63.1 (1604)
		(w/o mower)	in. (mm)	57.5 (1460)		
	Overall height	(w/ ROPS upright)	in. (mm)	75.4 (1915)		
(w/ ROPS folded)		in. (mm)	61.2 (1555)			
<b>Wheel base</b>		in. (mm)	55.5 (1410)	59.8 (1520)	55.5 (1410)	
<b>Tread</b>	Front	in. (mm)	38.4 (975)	42.1 (1070)	38.4 (975)	
	Rear	in. (mm)	45.3 (1150)			
<b>Tire size</b>	Front	15 x 6.0-6 Non-Flat				
	Rear	26 x 12.0-12				
<b>Weight (w/ mower)</b>	lbs. (kg)	1715 (778)	1770 (803)	1681 (763)		
<b>Transmission system</b>	2-HST w/ Gear reduction					
<b>Speed control</b>	2-hand lever					
<b>Travel speed range</b>	Forward	mph (km/h)	0-10.6 (0-17.0)			
	Reverse	mph (km/h)	0-5.3 (0-8.5)			
<b>Brake type</b>	Wet multi disks, foot applied, released					
<b>PTO</b>	Type	Shaft drive				
	Clutch type	Hydraulic independent PTO clutch with wet multi disks				
	PTO brake	Wet single disk				
<b>Mower deck</b>	Model	RCK60P-331Z	RCK72P-331Z	RCK60R-331Z		
	Mower lift system	Hydraulic				
	Mower deck type	Pro commercial—Fabricated deck				
	Deck depth	in. (mm)	6.5 (165)	5.5 (140)		
	Belt type	Multi-Belt				
	Deck steel thickness	in. (mm)	0.17 (4.2)			
	Anti-scalp roller	Swivel				
	Cutting width of mower		60 in.	72 in.	60 in.	
	Number of blades	3 blades				
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments				
	Mounting system of mower	Quick joint, parallel linkage				
	Blade tip speed (max.)		18200 FPM		17100 FPM	
<b>Engine stop system</b>	Key stop					
<b>Fuel tank capacity</b>	gals. (ltrs.)	12.9 (49)				
<b>Battery</b>	51R (12V, RC: 70 min., CCA: 475A)					
<b>Alternator capacity</b>	14 Volts at 14 Amps					
<b>Water temperature indicator</b>	Standard					
<b>Hour meter</b>	Standard					
<b>Fuel gauge</b>	Electric					

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.



# Z300 Series



# SPECIFICATIONS

## Specifications

Model		ZP330P-60	ZP330LP-72	
<b>Engine</b>	Model	Kubota WG972-GL-E3-ZG-1		
	Type	LPG, liquid-cooled (3 cyl.)		
	Max. horsepower (Gross)	31 HP@3600 rpm		
	Total displacement	58.7 cu.in. (962 cc)		
	Starting system	Key switch		
<b>Dimensions</b>	Overall length	91.7 in. (2329 mm)	95 in. (2414 mm)	
	Overall width	(w/ mower)	75.2 in. (1911 mm)	87.6 in. (2224 mm)
		(w/o mower)	66.1 in. (1679 mm)	
	Overall height	(w/ ROPS upright)	75.4 in. (1915 mm)	
(w/ ROPS folded)		64.8 in. (1645 mm)		
<b>Wheel base</b>		55.5 in. (1410 mm)	58.8 in. (1495 mm)	
<b>Tread</b>	Front	38.4 in. (975 mm)	42.1 in. (1070 mm)	
	Rear	45.3 in. (1150 mm)		
<b>Tire size</b>	Front	15 x 6.0-6 flat free		
	Rear	26 x 12.0-12		
<b>Weight (w/ mower) (with LPG fuel tank)</b>		1876 lbs. (851 kg)	1940 lbs. (880 kg)	
<b>Transmission system</b>		2-HST w/ Gear		
<b>Speed control</b>		2-hand lever		
<b>Travel speed range</b>	Forward	0-10.6 mph (0-17.0 km/h)		
	Reverse	0-5.3 mph (0-8.5 km/h)		
<b>Brake type</b>		Wet multi disks, foot applied, released		
<b>PTO</b>	Type	Shaft drive		
	Clutch type	Hydraulic independent PTO clutch with wet multi disks		
	PTO brake	Wet single disk		
<b>Mower deck</b>	Model	RCK60P-327Z	RCK72P-332Z	
	Mower lift system	Hydraulic		
	Mower deck type	Pro commercial— Fabricated deck		
	Deck depth	6.5 in. (165 mm)		
	Belt type	Multi-Belt		
	Deck steel thickness	0.17 in. (4.2 mm)		
	Anti-scalp roller	Rigid		
	Cutting width of mower	60 in.	72 in.	
	Number of blades	3 blades		
	Cutting height	1 in. ~ 5 in. / 1/4 in. increments		
	Mounting system of mower	Quick joint, parallel linkage		
	Blade tip speed (max.)	18500 FPM		
	<b>Engine stop system</b>		Key stop	
<b>Fuel tank capacity</b>		33.5 lbs x 2 (15.2 x 2 kg)		
<b>Battery</b>		51R (12 V, RC: 70 min., CCA: 475)		
<b>Alternator capacity</b>		14 Amps@14 Volts		

The company reserves the right to change the above specifications without notice. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. For complete operational information, the operator's manual should be consulted.